

CTCP-HM 1:3 Concentrate

Positive Plate Developer for CTCP Plates



Product Usage

Developer Concentrate for CTCP Plates positive working

Features and Benefits

- high buffer capacity in the plate processor - long lasting
- effective coating protection - long press stability of the plate
- low replenishing rate - constant developer power
- low or no sedimentations in the tank
- very economical as a 1:3 Concentrate

Packaging

10 liter cans

Directions

Developer: add 1 part of CTCP-HM 1:3 Concentrate to 3 parts of water Replenisher: add 1 part of CTCP-HM 1:3 Concentrate to 2 parts of water

start with the basic adjustment prescribed by the plate manufacturer

Temperature: 22°C-28°C, start with 25°C

Processor speed: 20-40 seconds, start with 25 seconds

Replenishing rate with CTCP-HM-R: 40-80ml/m², start with 60ml/m²

Stand-still replenishing: 40-100ml/hour, start with 80ml/h

Replenishing rate can be adjusted with the conductivity: 81mS

Technical Specifications

- Density: 1,33 g/cm³
- Color: clear
- Odour: mild - neutral
- Water miscible: yes
- labelling: C Corrosive

Storage and Shelf Life

Storage: not under 6°C, not above 40°C

Shelf Life: 12 months

keep container tightly closed

keep away from direct sun light