

# CTP-Smax|-Kmax|-Hmax

## Thermal Plate Developer



---

### Product Usage

Developer for Thermal-Plates (positive working) - ready to use

CTP-Smax	higher strength
CTP-Kmax	standard strength
CTP-Hmax	lower strength
CTP-Emax	soft strength

---

### Features and Benefits

- high buffer capacity in the plate processor - long lasting
- effective coating protection - long press stability of the plate
- top up replenishing with low rates - constant developer power
- or replenishing with Replenisher possible
- low sedimentations in the tank
- universal in use - for thermal and analogue plates

---

### Packaging

20 liter cans, 200 liter drums,  
1.000 liter IBC

---

### Directions

start with the basic adjustment prescribed by the plate manufacturer

Temperature: 22°C-28° C, start with 25° C

Processor speed: 20-40 seconds, start with 28 seconds

Replenishing rate: 100-180 ml/ m2, start with 140 ml/ m2

Stand-still replenishing: 150-180 ml/ hour, start with 150 ml/ h

With Replenisher: 40-80 ml/ m2 and 40-60 ml/ hour

---

### Technical Specifications

- Density: 1,09 g/cm3
- Color: clear
- Odour: mild - neutral
- Water miscible: yes
- labelling: Corrosive

---

### Storage and Shelf Life

storage: not under 6°C, not above 40°C

keep container tightly closed

keep away from direct sun light